



LOG-GEVITY™ LOG CHINKING PRODUCT SPECIFICATIONS

PRODUCT NAME

LOG-GEVITY™ LOG CHINKING

MANUFACTURER

American Building Restoration
Products, Inc.
9720 South 60th Street
Franklin, WI 53132
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696
www.abrp.com

PRODUCT DESCRIPTION

Log-Gevity™ Log Chinking has been engineered to be compatible with all of the **Log-Gevity™ Log Home Care Finishes**. Its special formula provides outstanding elasticity allowing log movement without losing its strong bonding characteristics. **Log-Gevity™ Log Chinking** is textured to produce a realistic, sand-like chinking material and is available in many **Log-Gevity™** coordinating colors.

Precautions: Read the entire material safety data sheet and product label for a more thorough evaluation of hazards. Fully protect all adjacent surfaces as well as general work area.

GENERAL DIRECTIONS

A test sample should be performed before beginning overall project to determine product compatibility and moisture content in logs. A 20 day adhesion test on a one-foot joint is recommended.

Surface Temperature: Should be between 40 degrees F. and 90 degrees F. when applying this product.

1. Thoroughly read the **Log-Gevity™ Chinking** product specification sheet prior to applying this product.
2. Start with clean, restored, non-green or weathered logs that have been treated with **Log-Gevity™ Log Stain & Stabilizer**. (See *product specification sheet for instructions*.)
3. For Tubes: Cut application tip on an angle. Puncture foil inside.
4. Apply chinking to clean, dry surfaces.
5. Use **Log-Gevity™ Chinking GLIDE** to make tooling smooth and easy. It also eliminates water runs and creates less mess.

Note: This product can be tooled with a trowel or sponge brush. Chinking should be tooled tightly to keep contact between 1/4 and 1/2 of the log surface.

TECHNICAL DATA

Packaging: 13 oz. tube, 36 oz. tube and gallon container.

HELPFUL PRODUCT GUIDELINES

- Apply over clean, dry surfaces. Surfaces should be free of oil, dirt or other foreign materials.
- Remove all weathered and deteriorated wood fiber to assure a sound bond to the substrate.
- Cleans up with soap and water.
- In severe conditions (under 50 degrees F. and/or over 70% humidity) full resistance to rain may take longer. Cover exterior walls with plastic.

CLEAN UP: Use mineral spirits or dish detergent and water. Should **Log-Gevity™**

Log Chinking come in contact with surfaces such as glass, paint, metal, caulking or rubber, remove immediately with dish detergent. If a spill is dry, clean it with mineral spirits.

STORAGE: Keep tube or container closed when not in use. Store in cool place. **This product should be kept out of reach of children and stored away from food.**

DISPOSAL: Do not reuse empty container or tube. Wrap container and place in trash. Leaking or damaged containers should be placed in a plastic bag and discarded. Contact local, state, or federal agencies to ensure compliance of proper disposal methods and respective regulations.

NOTICE: The information and recommendations made herein are based on ABRP, Inc., research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of purchase. The purchaser of

this product shall be entitled to the following, if the product herein is shown to be defective: **ABRP, Inc.**, at its option, will either replace the product or refund the purchase price. Contact **ABRP, Inc.**, to make claim under this warranty. The purchaser must have proof of purchase from label and original sales receipt. Proper surface preparation is essential to the applicability of this warranty. Read and follow label directions.

ABRP, Inc., shall not be liable for incidental, consequential or indirect damage arising from the use of this product or the cost of labor involved in its application.

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

No other warranties are made,

expressed or implied, including without limitation warranties as to MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of **ABRP, Inc.**, products.

Some states do not allow the exclusion or limitation of incidental or consequential damages so the above limitation or exclusion may not apply to the purchaser. This warranty gives the purchaser specific legal rights as well as other rights which may vary from state to state.

TECHNICAL SERVICES

ABRP, Inc., employs in field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications and brochures are available upon request.

Visit **www.Log-Gevity.com** for additional information on the complete Log-Gevity Product Line or for other log home restoration and preservation products.

For more information on many of the specialty building restoration products available from ABRP, Inc., visit www.abrp.com or e-mail ABRP, Inc. at support@abrp.com

© Copyright 2005 ABR Products, Inc.

